### The Anderson Family Ground Power Cable Assemblies



#### Attachable® and Over Molded Cable Assemblies

Cable assemblies are fabricated to the exacting requirements of MIL-C-7974D. Anderson Airmotive Products is a qualified source of supply for MS25019, MS90328, MS21378, and MS90347 assemblies.

In addition, Anderson can supply special cable configurations or lengths to meet your requirements. Contact the factory or your local Authorized Distributor for additional information.


All Anderson cable assemblies feature silver plated high conductivity contacts with finger proof safety insulators and cable qualified to the latest military specification MIL-C-5756C; Composite Cables are UL listed. Plugs are molded proprietary synthetic elastomer for severe wear and tear applications. All these features insure that our cable assemblies are the safest, most flexible and longest lasting cable assemblies available today.

Our family of power cables is unequaled in the industry. Anderson Airmotive is the only company to offer you a choice of:

- (1) making/repairing your own ground power cables with our family of high quality and durable Attachable ®plugs, or
- (2) buying a wide variety of new cable assemblies with either Attachable® or Overmolded plugs, from the factory.



AC output cable assemblies from 110/200 VAC and 230/400VAC to 600V input cable assemblies with quick change Wear noses, EcoNose, Temperature sensing switch plugs with modular components and many cable options.




DC output cable assemblies from 28VDC, 80VDC and 270VDC with quick Change Wear Noses, Eco Noses and many cable options.

# DC AIRCRAFT GROUND POWER CABLE ASSEMBLIES 3-POLE



#### 2 Wire R65 28V DC



Electrical Ratings:30°C rise Power Components, 450A Continuous 1500A for 1 minute, Control Components, 35A continuous

PART NUMBER	LENGTH FEET/METERS	MILITARY PART NO.	CABLE DESCRIPTION	WEIGHT LBS (KG)	ASSEMBLY CONFIGURATION
R65G1E-20AorM R65G1E-30AorM R65G1E-40AorM R65G1E-60AorM R65G1E-80AorM R65G1E-100AorM R65G1E-2AorM	20 (6) 30 (9) 40 (12) 60 (18) 80 (24) 100 (30) 2 (0.7)	MS90347-7AorM MS90347-8AorM MS90347-9AorM MS90347-10AorM MS90347-11AorM MS90347-12AorM MS90347-25AorM	2-1/0 (50mm) AWG SINGLE CONDUCTORS, NO CONTROL LEAD, SILVERPLATED CONTACTS, AND NON-METALLIC BANDS SPLICE KIT	26 (12) 36 (16) 46 (21) 67 (30) 87 (40) 107 (49) 7 (3)	+ R
R65G2E-20AorM R65G2E-30AorM R65G2E-40AorM R65G2E-60AorM R65G2E-80AorM R65G2E-100AorM R65G2E-2AorM	20 (6) 30 (9) 40 (12) 60 (18) 80 (24) 100 (30) 2 (0.7)	MS90347-13AorM MS90347-14AorM MS90347-15AorM MS90347-16AorM MS90347-17AorM MS90347-18AorM MS90347-26AorM	2-2/0 (70mm) AWG SINGLE CONDUCTORS, NO CONTROL LEAD, SILVERPLATED CONTACTS, AND NON-METALLIC BANDS SPLICE KIT	32 (15) 45 (21) 58 (26) 84 (38) 110 (50) 136 (67) 8 (4)	
R65G3E-20AorM R65G3E-30AorM R65G3E-40AorM R65G3E-60AorM R65G3E-80AorM R65G3E-100AorM R65G3E-2AorM	20 (6) 30 (9) 40 (12) 60 (18) 80 (24) 100 (30) 2 (0.7)	MS90347-19AorM MS90347-20AorM MS90347-21AorM MS90347-22AorM MS90347-23AorM MS90347-24AorM MS90347-27AorM	2-4/0 (120mm) AWG SINGLE CONDUCTORS, NO CONTROL LEAD, SILVERPLATED CONTACTS, AND NON-METALLIC BANDS SPLICE KIT	45 (20) 65 (29) 84 (38) 123 (56) 162 (74) 201 (91) 9 (4)	

Cable assemblies are available with Attachable® plug types as well as integrally Over Molded connectors. Other assemblies available for different cable sizes and configurations

R65Gxx(E)(F)(EN)(A)(M)

A= Attachable® Head M=Over Molded Head

(E) Standard Contact (F) Euro Contact (EN) EcoNose

ATTACHABLE<sup>®</sup> is a registered trademark of Anderson Airmotive Products.

## Over-Molded Cable Assemblies

## **28VDC**







R765 4-6 Wire with EcoNose®



R65 / R71 3 Wire