### THE ANDERSON FAMILY RECEPTACLES

Ground Power Receptacles are located on the aircraft or other devices and receive the power input from a ground source to recharge and operate electrical accessories. Anderson offers the largest selection of receptacles ranging from 28V DC to 270V DC and 110V AC to 400V AC accommodating all your power needs. Varieties include male and female designs.

Anderson Airmotive DC and AC receptacles are manufactured to specification MIL-C-81790 and are listed on the Qualified Products List. Bases are molded of glass reinforced material for low moisture absorption and high strength. The copper power and brass control contacts are machined and silverplated to MS

#### tolerances.

The shield, when applicable, is of anodized aluminum to guide plug insertion and guard against misalignment. Studs and contact nuts for lug connections are located at the rear of the receptacle.



#### Receptacle Performance to QPL MIL-C-81790 (AS81790)

Dielectric Withstand2500VRMS WITH< 1 milli-amp leakage</th>Current Rating - Power Contacts450A continuous (> than 1 hour) 1500A for 1 minuteCurrent Rating - Control Contacts35A continuous auxiliaryFlexural Strength3500 lbs (1590 Kg)Thermal Shock-65° to +200°CImpact Strength - Power ContactsWithstands impact of 10 lb weight (4.5KG) dropped from 24 inches (60 cm)Impact Strength - Control ContactsWithstands impact of 10 lb weight (4.5KG) dropped from 12 inches (30 cm)

## 80 VDC Fast Charge; 230/400V AC RECEPTACLES 80 VDC Fast Charge; 270 VDC; 400 VDC

Ground Power Receptacles are located on the aircraft or other devices and receive the power input from a ground source to recharge and operate electrical accessories. Anderson offers the largest selection of receptacles ranging from 28V DC, 80V DC, 400V DC, 270V DC and 110V AC to 400V AC accommodating all your power needs.

#### 80V/270V



**Receptacle\*** 270V 3-8358P1 80VFC 3-8358P2

400V/400A DC 9 Pin Fast Charge



Receptacle with Shield 270V 4629B 80VFC-4630B



Shield 2-8356P1 2-8356P1SC with Snap Cover



**Rear Cover** 4634B

270V/80V DC

3-8358P1 + Terminal MJ8 - Terminal MJ6

3-8358P2 + Terminal MJ8 - Terminal MJ8




Receptacle 3-8400MD1



Shield 2-8356P2



Receptacle with Shield



4635B



Shield 2-6976P1



**Snap Cover** 2-6976P1SC

#### 230/400V AC



Receptacle 3-4985G1



Receptacle with Shield MS21379

## **Electric Vehicle Charging Connectors**

### **Charging Power Plugs and Cable Assemblies**

### **Benefits:**

- Silver-plated contacts for charging up to 450A
- Full line of integral molded plugs and receptacles
- Designed for low insertion force
- Multiple options include sensors and control mechanisms
- Excellent resistance to moisture/chemicals and severe wear and tear

#### **Battery Connectors**





- Versatile, secure, high current corkscrew connector suitable for:
  - Weatherproof battery charger and inter-component connections
  - Stand-by power connector in computer systems
  - Ground power connector in marine, air and rail transport
  - Wherever hydraulic fluids, oils, acids and other such potentially destructive elements could shorten the connector life

#### **ORDER INFORMATION:**

Battery ConnectorR121 orR125G## - Cable IdentifierBattery Receptacle4657BX



### **Fast Charge Power Cables and Receptacles**

- High current 6 and 9 Pin plugs and receptacles
- Multiple cable configurations
- Capable of 80VDC/150A and 400VDC/450A



#### **ORDER INFORMATION:**

Fast Chrg Cable	R270 Gxx E - M	6 Pin	xx – Cable Config
Fast Chrg Cable	R80 G103	9 Pin	
Receptacle w/ Shield	4630B	6 Pin	
Receptacle w/ Shield	4635B	9 Pin	

ANDERSON AIRMOTIVE PRODUCTS Co., Inc. 994 Jefferson Street, Fall River, MA 02721 • Tel (508) 646-0950 / Fax (508) 646-0966 E-mail : sales@andersonairmotive.com • www.andersonairmotive.com

# **Fast Charge Over-molded Cables and Receptacles**



R270 Gxx E - M	xx – Cable Configuration
R270 Kit 1Y	Replacement Nose







<u>9 Pin</u> 400VDC 400A

ORDER INFORMATION:

R80 G103

#### ANDERSON AIRMOTIVE PRODUCTS Co., Inc. 994 Jefferson Street, Fall River, MA 02721 • Tel (508) 646-0950 / Fax (508) 646-0966

E-mail: sales@andersonairmotive.com • www.andersonairmotive.com